

DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER) BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

MIAMI-DADE COUNTY PRODUCT CONTROL SECTION 11805 SW 26 Street, Room 208 T (786) 315-2590 F (786) 315-2599

www.miamidade.gov/economy

Asselin, Inc.

2870 Peachtree Rd. NW, #714

Atlanta, GA 30305

Scope:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Series "Manoir" Inswing Wood Casement Window - L.M.I.

APPROVAL DOCUMENT: Drawing No. **08-01856**, titled "Manoir In-Swing Casement Single & Double", sheets 1 through 8 of 8, dated 11/26/12, with revision A dated 07/25/13, prepared by manufacturer, signed and sealed by Luis R. Lomas, P.E., bearing the Miami–Dade County Product Control Revision stamp with the Notice of Acceptance number and expiration date by the Miami–Dade County Product Control Section.

MISSILE IMPACT RATING: Large and Small Missile Impact Resistant

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state, model/series, and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA# 13-0327.04 and consists of this page 1 and evidence pages E-1 and E-2, as well as approval document mentioned above.

The submitted documentation was reviewed by Manuel Perez, P.E.

(MIAMI-DADE COUNTY)
APPROYED

1/1/20/14

NOA No. 14-0505.06 Expiration Date: October 03, 2018 Approval Date: August 07, 2014

Page 1

Asselin, Inc.

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

A. DRAWINGS

- 1. Manufacturer's die drawings and sections.
- Drawing No **08-01856**, titled: "Manoir In-Swing Casement Single & Double", sheets 1 through 8 of 8, dated 11/26/12, with revision A dated 07/25/13, prepared by manufacturer, signed and sealed by Luis R. Lomas, P.E. (Submitted under previous NOA# 13-0327.04)

B. TESTS

- 1. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202–94
 - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94
 - 4) Large Missile Impact Test per FBC, TAS 201-94
 - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94
 - 6) Forced Entry Test, per FBC 2411 3.2.1, TAS 202-94

along with marked-up drawings and installation diagram of a series "Manoir" in-swing wood casement window (XX), prepared by Hurricane Test Laboratory, LLC, Test Report No. **HTL-G511-0204-11**, dated 02/28/11 to 03/03/11, signed and sealed by Vinu J. Abraham, P.E.

(Submitted under previous NOA# 13-0327.04)

C. CALCULATIONS

- 1. Anchor calculations and structural analysis, complying with FBC–2010, dated 11/21/12, prepared, signed and sealed by Luis R. Lomas, P.E. (Submitted under previous NOA# 13-0327.04)
- 2. Glazing complies with ASTM E1300-04.

D. QUALITY ASSURANCE

1. Miami-Dade Department of Regulatory and Economic Resources (RER)

E. MATERIAL CERTIFICATIONS

1. Notice of Acceptance No. 12-1231.10 issued to Eastman Chemical Company (MA) for their "Saflex Clear and Color Glass Interlayers" dated 03/28/13, expiring on 05/21/16.

Manuel Perez, P.E. Product Control Examiner NOA No. 14-0595.06

Expiration Date: October 03, 2018 Approval Date: August 07, 2014

Asselin, Inc.

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

F. STATEMENTS

- 1. Statement letter of conformance, complying with FBC-2010 and FBC-5th Edition (2014), and of no financial interest, dated April 22, 2014, signed and sealed by Luis R. Lomas, P.E.
- 2. Laboratory compliance letter for Test Report No. HTL G511-0204-11, issued by Hurricane Test Laboratory, LLC, dated 04/20/12, signed and sealed by Vinu J. Abraham, P.E.

(Submitted under previous NOA# 13-0327.04)

3. Distributor Agreement between Asselin, SAS, Thouars Ceder, France and Asselin, Inc., Atlanta, Georgia, USA, dated 03/11/13, signed by Francois Asselin. (Submitted under previous NOA# 13-0327.04)

G. OTHERS

1. Notice of Acceptance No. 13-0327.04, issued to Asselin, Inc., for their Series "Manoir" Inswing Wood Casement Window – L.M.I.", approved on 10/03/13 and expiring on 10/03/18.

Manuel Perez, P.E.
Product Control Examiner
NOA No. 14-0595.06
Expiration Date: October 03, 2018

Approval Date: August 07, 2014

NOTES

- 1. THE PRODUCT SHOWN HEREIN IS DESIGNED AND MANUFACTURED TO COMPLY WITH REQUIREMENTS OF THE FLORIDA BUILDING CODE INCLUDING THE HVHZ.
- 2. WOOD FRAMING AND MASONRY OPENING TO BE DESIGNED AND ANCHORED TO PROPERLY TRANSFER ALL LOADS TO STRUCTURE. FRAMING AND MASONRY OPENING IS THE RESPONSIBILITY OF THE ARCHITECT OR ENGINEER OF RECORD.
- 3. 1X BUCK OVER MASONRY/CONCRETE IS OPTIONAL. WHERE 1X BUCK IS NOT USED DISSIMILAR MATERIALS MUST BE SEPARATED WITH APPROVED COATING OR MEMBRANE. SELECTION OF COATING OR MEMBRANE IS THE RESPONSIBILITY OF THE ARCHITECT OR ENGINEER OF RECORD.
- 4. ALLOWABLE STRESS INCREASE OF 1/3 WAS NOT USED IN THE DESIGN OF THE PRODUCT SHOWN HEREIN. WIND LOAD DURATION FACTOR Cd=1.6 WAS USED FOR WOOD ANCHOR CALCULATIONS.
- 5. FRAME MATERIAL: WOOD MOABI (SPECIFIC GRAVITY G=0.87)
- 6. UNITS MUST BE GLAZED PER ASTM E1300-04, SEE SHEET 3 FOR GLASS OPTIONS.
- 7. APPROVED IMPACT PROTECTIVE SYSTEM <u>IS NOT REQUIRED</u> FOR THIS PRODUCT IN WIND BORNE DEBRIS REGIONS.
- 8. SHIM AS REQUIRED AT EACH INSTALLATION ANCHOR WITH LOAD BEARING SHIM. SHIM WHERE SPACE OF 1/16" OR GREATER OCCURS. MAXIMUM ALLOWABLE SHIM STACK TO BE 1/4".
- 9. FOR ANCHORING INTO WOOD FRAMING OR 2X BUCK USE #10 WOOD SCREWS WITH 1/2" MINIMUM EDGE DISTANCE AND SUFFICIENT LENGTH TO ACHIEVE A 1 3/8" MINIMUM EMBEDMENT INTO SUBSTRATE. LOCATE ANCHORS AS SHOWN IN ELEVATIONS AND INSTALLATION DETAILS.
- 10. FOR ANCHORING INTO MASONRY/CONCRETE USE 3/16" TAPCONS WITH SUFFICIENT LENGTH TO ACHIEVE A 1 1/4" MINIMUM EMBEDMENT INTO SUBSTRATE WITH 2 1/2" MINIMUM EDGE DISTANCE. LOCATE ANCHORS AS SHOWN IN ELEVATIONS AND INSTALLATION DETAILS.
- 11. FOR ANCHORING INTO METAL STRUCTURE USE #10 SMS OR SELF DRILLING SCREWS WITH 3/4" MINIMUM EDGE DISTANCE AND SUFFICIENT LENGTH TO ACHIEVE 3 THREADS MINIMUM BEYOND STRUCTURE INTERIOR WALL. LOCATE ANCHORS AS SHOWN IN ELEVATIONS AND INSTALLATION DETAILS.
- 12. ALL FASTENERS TO BE CORROSION RESISTANT.
- 13. INSTALLATION ANCHORS SHALL BE INSTALLED IN ACCORDANCE WITH ANCHOR MANUFACTURER'S INSTALLATION INSTRUCTIONS AND ANCHORS SHALL NOT BE USED IN SUBSTRATES WITH STRENGTHS LESS THAN THE MINIMUM STRENGTH SPECIFIED BELOW:
 - A. WOOD MINIMUM SPECIFIC GRAVITY OF G=0.42
 - B. CONCRETE MINIMUM COMPRESSIVE STRENGTH OF 3,192 PSI.
 - C. MASONRY STRENGTH CONFORMANCE TO ASTM C-90, GRADE N, TYPE 1 (OR GREATER).
 - D. METAL STRUCTURE: STEEL 18GA, 33KSI OR ALUMINUM 6063-T5 1/8" THICK MINIMUM

| REVISIONS | | | | | | |
|-----------|-------------------------|----------|----------|--|--|--|
| REV | DESCRIPTION | DATE | APPROVED | | | |
| Α | REVISED PER MD COMMENTS | 07/25/13 | R.L. | | | |

PRODUCT REVISED as complying with the Florida Building Code Acceptance No 14-0505.0

By Mull Sy Miabii Dade Product Control

SIGNED: 07/29/2013


| | TABLE OF CONTENTS | | | | |
|-------|-------------------|-------------------------|--|--|--|
| SHEET | NO. | DESCRIPTION | | | |
| 1 | F | NOTES | | | |
| 2 | | ELEVATIONS | | | |
| 3 - | 4 | B.O.M. & CROSS SECTIONS | | | |
| 5 - | 6 | INSTALLATION DETAILS | | | |
| 7 | | HARDWARE | | | |
| 8 | | COMPONENTS & HARDWARE | | | |


Approved as complying with the Florida Building Code
Date Oct. 3, 2013
NOA# 13-03/7.03
Miami Dade Product Control
By Mallul USO


ASSELIN, INC. 2870 PEACHTREE RD. NW, #714 ATLANTA, GA 30305


MANOIR IN-SWING CASEMENT SINGLE & DOUBLE NOTES

DRAWN: DWG NO. 08-01856 REV V.L. 08-01856 A










REVISIONS APPROVED DESCRIPTION DATE REVISED PER MD COMMENTS 07/25/13 R.L.

DOUBLE VENT HORIZONTAL SECTION



SINGLE VENT HORIZONTAL SECTION

PRODUCT REVISED as complying with the Florida Building Code
Acceptance No 14-0505.0 Expiration Date

By Maule Percondition Miamy Dade Product Control


SIGNED: 07/29/2013


Approved as complying with the Florida Building Code
Date OCT. 3, 2013
NOAH 13-0327.04
Miasai Dade Product Control


ASSELIN, INC. 2870 PEACHTREE RD. NW, #714 ATLANTA, GA 30305

MANOIR IN-SWING CASEMENT SINGLE & DOUBLE CROSS SECTIONS


DWG NO. DRAWN: 08-01856 SCALE NTS DATE 11/26/12 SHEET 4 OF 8








| | REVISIONS | | | | | |
|-----|-------------------------|----------|----------|--|--|--|
| REV | DESCRIPTION | DATE | APPROVEO | | | |
| Α | REVISED PER MD COMMENTS | 07/25/13 | R.L. | | | |



RECESSED CREMONE

TYPE 776 FROM FERCO

22) SURFACE MOUNTED CREMONE
TYPE REMY GARNIER FULL ROD 18 MM



23) STEEL HINGE TYPE 140 X 55" LOUTRE PRODUCT REVISED as complying with the Florida Building Code Acceptance No 4-0505.0 Expiration Date Oct.

By Manuel Str Miami Dade Product Control

SIGNED: 07/29/2013

Approved as complying with the Florida Building Code
Date Oct. 3, 2013
NOA# 13-0327.04
Minmi Dade Product Control

By Mallind Disc.

ASSELIN, INC. 2870 PEACHTREE RD. NW, #714 ATLANTA, GA 30305

MANOIR IN-SWING CASEMENT SINGLE & DOUBLE HARDWARE

DRAWN: DWG NO. 08-01856 REV A SCALE NTS DATE 11/26/12 SHEET 7 OF 8

* No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No. 6251X *

No.

